



# TR4055

## Standard Wax Technical Data Sheet



### Product Description

DNP's newest wax product features a blend of waxes and a unique resin that are combined in an ink that flows smoothly at low print energy to give uniform coverage on lower end substrates. TR4055 also incorporates technology designed to control and dissipate static charges and a backcoat proven to protect your printhead. Specially formulated to provide excellent performance in a broad range of applications, TR4055 sets the beyond standard for everyday thermal transfer printing.

### Applications



Food & Beverage



Inventory & Logistics



Retail

### Recommended Substrates

#### Paper

- Coated paper
- Coated Tag
- Uncoated paper
- Uncoated Tag

### Performance Characteristics

- Suitable for a wide range of applications
- Scratch resistance
- Smudge resistance
- Capable of print speeds up to 12 IPS
- Dark glossy printed image
- Halogen-free

More Info



## RIBBON PROPERTIES

Description	Result	Test Method
Ink	Wax	
Color	Black	Visual
Total Thickness	7.8 ± 0.6μ	Micrometer
Base Film Thickness	4.8 ± 0.3μ	Micrometer

## DURABILITY OF PRINTED IMAGE

Description	Result	Test Method
Print Density	> 1.80	Densitometer
Smudge Resistance	A*	Colorfastness Tester - 50 Cycles @ 500 Grams with Cotton Cloth
Scratch Resistance	A*	Colorfastness Tester - 20 Cycles @ 200 Grams with Stainless Steel Pointed Tip

Label Stock: Coated Paper

Print Speed: 6 IPS

\*American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.



The information on this data sheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

**PT. Mitra Nippon Printing Indonesia**

Kawasan Industri Multiguna 2, Jalan Tanjung No. 3-5, Cikarang Selatan 17530, Indonesia.

**DNP IMAGINGCOMM ASIA SDN. BHD.**